AHI

Hardware independent audio for Amiga
AHI User's Guide, version 4.2

Martin 'Leviticus' Blom

Copyright © 1994-1997 Martin Blom. This publication may not be modified in any way, including translation, without prior consent, in writing, by the author.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

This publication is provided by the author "as is" and any express or implied warranties, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose are disclaimed. In no event shall the author be liable for any direct, indirect, incidental, special, exemplary, or consequential damages (including, but not limited to, procurement of substitute goods or services; loss of use, data, or profits; or business interruption) however caused and on any theory of liability, whether in contract, strict liability, or tort (including negligence or otherwise) arising in any way out of the use of this publication, even if advised of the possibility of such damage.

1 Overview

The *Amiga* has always had excellent sound capabilities. In 1986, they were awesome. Today, well... Perhaps not awesome, but still very good. The OS interface, `audio.device` has however never been as good as it could have been. It is tied hard to the underlying hardware, and doesn't work very well for music. This has led to a situation where most audio programs only use `audio.device` to allocate the audio resource, and then poke around in the hardware registers—making it next to impossible to replace the *Paula* chip[1].

There have been attempts to write an `audio.device` clone that uses a sound card instead of Paula, but so far nobody has succeeded. It is definitely possible, but the question is if it is worth the trouble—too many of the programs bang the hardware.

Entering AHI[2]. AHI is a new audio subsystem, designed to be flexible, hardware independent, expandable and future safe. It is designed with real-time applications in mind. It is designed to play *modules*[3] and sound effects as efficient as possible, taking advantage of modern DSP-based sound cards.

Yet AHI allows applications that don't need full control over the audio hardware to share the resource, so that many different programs can play and record sound at the same time, without conflicts.

As a user you will hopefully not see much of AHI, other than the audio mode requesters. They works almost exactly like screen mode requesters.

AHI was never supposed to be *the* standard for hardware independent audio. It was meant as a temporary solution until *Amiga Technologies* delivered an official standard. However, the situation looks worse and worse for every day that passes by, and this may be all you will ever get.

[1] Paula is one of the custom chips, and she is responsible for the sound (and more). Unfortunately, this chip has not been updated since the very first Amiga was released.

[2] The name AHI was chosen because the functions in the system had to have a prefix, and the author couldn't come up with anything better than *Audio Hardware Interface*, something that he has regretted ever since. The suggested pronunciation is "atchii", as in "God bless!".

[3] Originally designed in 1986 by Karsten Obarski, modules has become a de facto standard for game and demo music. The original format has been improved many times, and many new music formats have—more or less—been derived from it, including the popular *S3M* and *XM* formats.

2 Distribution

Copyright © 1994-1997 Martin Blom

Ahi is available as *freeware*. That is, it may be freely distributed in unmodified form with no changes what so ever, but you may not charge more than a nominal fee covering distribution costs. However, donations are welcome (see Chapter 3 [Donations], page 5).

If you use this software in a commercial or shareware software product, please consider giving the author (see Chapter 5 [The Author], page 15)—and preferably each one of the contributors (see Section 6.1 [Contributors], page 17) too—an original or registered version of your work.

If you wish to distribute this software with a hardware product, contact the author (see Chapter 5 [The Author], page 15). Distribution of AHI with hardware products is *not* free.

This software is provided by the author and contributors "as is" and any express or implied warranties, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose are disclaimed. In no event shall the author or contributors be liable for any direct, indirect, incidental, special, exemplary, or consequential damages (including, but not limited to, procurement of substitute goods or services; loss of use, data, or profits; or business interruption) however caused and on any theory of liability, whether in contract, strict liability, or tort (including negligence or otherwise) arising in any way out of the use of this software, even if advised of the possibility of such damage.

3 Donations

–Ahi is available for personal use without any charges. I strongly believe in free software, and I use free high-quality software tools daily. But I live, like all of us, in a real world. As a student, my income doesn't even suffice for the rent, and much less food, course literature and entertainments. Therefore I ask, if you like this software, please consider showing your gratitude by making a small donation (see Chapter 5 [The Author], page 15 for my address).

Martin

4 System description

4.1 AddAudioModes

Format [FILES <file|pattern>] [QUIET] [REFRESH] [REMOVE] [DBLSCAN]

Template FILES/M,QUIET/S,REFRESH/S,REMOVE/S,DBLSCAN/S

Purpose To build and remove a list of audio modes that AHI can understand.

Path C:ADDAUDIOMODES

Specification

`AddAudioModes` is used to build and remove a list of audio modes that AHI can understand. The definitions of the audio modes are stored in '`DEVS:Audiomodes`' (see Section 4.4.2 [The Mode Descriptors], page 12). Normally you don't have to run this program, since `ahi.device` automatically reads all mode descriptors when it is used for the first time. It can, however, be useful in installation scripts.

The '`FILES`' option specifies with descriptor(s) to be added to the current mode list.

The '`QUIET`' option, if specified, will suppress error and output messages.

The '`REFRESH`' option, if specified, will scan '`DEVS:Audiomodes`' and add all descriptors found there to the current mode list.

The '`REMOVE`' option, if specified, will flush the current audio mode list from memory.

The '`DBLSCAN`' option does not have anything to do with the audio mode list. If specified, it will open and then immediately close a native, double-scan screen. On some systems using a graphic card, this will enable >28 kHz sample frequencies with the native audio. You need an appropriate monitor driver in '`DEVS:Monitors`' to make it work.

4.2 AHI

Format [FROM <filename>] [EDIT] [USE] [SAVE] [PUBSCREEN <public screen name>

Template FROM,EDIT/S,USE/S,SAVE/S,PUBSCREEN/K

Purpose To specify default audio options

Path SYS:Prefs/AHI

Specification

`AHI` without any arguments or with the '`EDIT`' argument opens the AHI preferences editor. The '`FROM`' argument lets you specify a file to open. This must be a file that was previously saved with the '`Save As...`' menu item of the AHI preferences editor. For example, if you have saved a special configuration of the AHI preferences editor to a file in the '`Presets`' drawer, you can use the '`FROM`' argument to open that file. If the '`USE`' switch is also given, the editor will not be opened, but the settings in the '`FROM`' file will be used. If the '`SAVE`' switch is given, the editor will not open, but the settings in the '`FROM`' file will be saved. The '`PUBSCREEN`' option allows you to specify a public screen on which the program will open its window.

Example:

```
AHI Prefs/Presets/AHI.Delfina USE
```

loads and uses the specifications saved in the 'AHI.Delfina' file. If the system is rebooted, the last saved specifications will be loaded.

Note that the preferences program requires bgui.library version 41[1].

4.2.1 Menus

4.2.1.1 'Project' Menu

The 'Project' menu options let you save the editor settings to a specific file and open previously saved files.

'Open...' Loads the information from a specified preset file.

'Save As...'
Specify the preset file in which to save the currently displayed settings. The requester provides a default file name in the 'Presets' drawer. If you want to change it, type in the full path to a different file and select 'OK'.

'About...' Shows the credits.

'Quit' Exits the editor without performing any changes (the same as the 'Cancel' gadget).

4.2.1.2 'Edit' Menu

The 'Edit' menu options allow you to restore previously used settings or the default settings. The options are:

'Reset to Default'
Returns the editor settings to the default settings.

'Last Saved'
Returns the editor settings to the last settings you saved.

'Restore' Returns the editor to the settings displayed when the editor first opened.

4.2.1.3 'Settings' Menu

The 'Settings' menu contains the 'Create Icons?' item that allows you to save project icons representing your editor settings in the same drawer as your files. For example, if you save the specifications to the 'SYS:Prefs/Presets/AHI.pre' file, the icon for the file appears in the 'Presets' window. Double-click on the icon to activate the file's settings.

[1] BGUI is Copyright 1996-1997 Ian J. Einman

4.2.1.4 'Help' Menu

The 'Help' menu's items let you view the on-line "AHI User's Guide" using AmigaGuide.

'Help...' Brings up the chapter about the preferences program (this chapter).

'AHI User's Guide...'
Brings up the first page of "AHI User's Guide".

'Concept Index...'
Brings up the index of "AHI User's Guide".

4.2.2 Pages

The preferences program's GUI is divided in two pages:

4.2.2.1 'Mode settings' Page

On this page you select which audio mode to use. You can select audio mode for both low-level programs ('Music unit') and other programs ('Unit n') that don't require low-level audio access such as the AUDIO: device (see Section 4.3 [AHI-Handler], page 10), sample players etc. You can also select the sample mixing (and recording) frequency to use and how many channels you wish use[2]. Furthermore, you can set three hardware properties of your sound hardware, namely the *output volume*, *monitor volume* and *input gain*. Finally, you can select which input and output connectors you wish to use.

The 'Music unit' is the defaults for low-level programs. Such programs often have an audio mode requester that lets you chose an audio mode. If you chose 'Default audio mode' from this requester, these settings will be used. Note that the number of channels is not selectable here, it's up to the application program to decide how many channels to use.

4.2.2.2 'Advanced settings' Page

This page contains some options that should not be used if you don't understand them.

'Debug level'
Sets the debug level for AHI. If not 'None', AHI will print debug information to the serial port.

'Echo' On slow processors (like anything below a MC68040) echo can take so much CPU power that it becomes unusable, and can therefore be disabled. As an alternative, echo can be done 'Fast', which means that the parameters will be twisted in order to gain speed. The result may not be what the composer or programmer wanted, but at least it's echo.

[2] The more channels you select, the more sounds can you play at the same time. However, due to the nature of sound mixing, the volume will decrease as well. If you try to play more sounds at the same time than there are channels, the least important sounds will be muted until the other sounds have finished playing.

'`Surround in "Fast" modes`'
: In modes that use multiplication tables (the so-called "fast" modes) all surround sounds have to be mixing without using tables. In order to make mixing as fast as possible, surround sounds can be forced to ordinary ones by disabling them.

'`CPU usage limit`'
: Some hardware drivers (but not all) can be told not to use more that a given percentage of the available CPU time in order to prevent lockups. If your mouse pointer freezes when playing music, reduce the limit slightly. If on the other hand the sound becomes cut and distorted, you can try to increase the limit—but remember that you risk locking up the computer!

4.3 AHI-Handler

The `AHI-Handler` is an I/O mechanism that is used to play and record sounds. The `AHI-Handler` is normally mounted as `AUDIO:` at startup time, or later by double-clicking on its icon or by giving the following command in a Shell window: *`mount AUDIO:`* ⟨RET⟩.

The DOSDriver entry is:

```
Handler         = L:AHI-Handler
Stacksize       = 4096
Priority        = 5
GlobVec         = -1
```

When the device is mounted, you can read from the device to record and write to it to play. Options can be given like this:

```
"AUDIO:PRIORITY=1 VOLUME=50"
```

All slashes ('`/`') in the name will be translated to spaces. Thus, if you use slashes instead of spaces, you don't have to use quotes around the name:

```
AUDIO:PRIORITY/1/VOLUME/50
```

The full template for reading is:

```
B=BITS/K/N,C=CHANNELS/K/N,F=FREQUENCY/K/N,T=TYPE/K,L=LENGTH/K/N,
S=SECONDS/K/N,BUF=BUFFER/K/N,UNIT/K/N
```

The full template for writing is:

```
B=BITS/K/N,C=CHANNELS/K/N,F=FREQUENCY/K/N,T=TYPE/K,V=VOLUME/K/N,
P=POSITION/K/N,PRI=PRIORITY/K/N,L=LENGTH/K/N,S=SECONDS/K/N,
BUF=BUFFER/K/N,UNIT/K/N
```

'`BITS`' can be one of 8, 16 or 32. '`CHANNELS`' can be either 1 for mono or 2 for stereo. The '`FREQUENCY`' is in Hertz, '`TYPE`' is one of '`SIGNED`', '`AIFF`' or '`AIFC`'. '`VOLUME`' ranges from 0 (silence) to 100 (full volume), and '`POSITION`' ranges from −100 (far left) via 0 (center) to 100 (far right).

The 'PRIORITY' can be from −128 to 127 (unstoppable). 'LENGTH' is how many bytes you wish to read or write, and 'SECONDS' is the same, but in seconds instead of bytes. The 'BUFFER' size is specified in bytes. Note that two buffers are always used, which means that the memory usage will be two times BUFFER. 'UNIT' selects which `ahi.device` unit to use.

The default options for reading are 'BITS=8 CHANNELS=1 FREQUENCY=8000 TYPE=SIGNED LENGTH=very-very-much BUFFER=32768 UNIT=0'.

The default options for reading are 'BITS=8 CHANNELS=1 FREQUENCY=8000 TYPE=<none> VOLUME=100 POSITION=0 PRIORITY=0 LENGTH=very-very-much BUFFER=32768 UNIT=0'.

If 'TYPE' is not specified, the default behavior is to identify the data stream as *IFF-AIFF* or *IFF-AIFC*. If so, the default values of 'BITS', 'CHANNELS', 'FREQUENCY' and 'LENGTH' will taken from the file. You can still override them if you wish. If the stream could not be identified, the data format is assumed to be 'SIGNED'.

Both when reading and writing the sample rate will be converted on the fly to what the underlying hardware is configured to. Normally this is not a big problem when writing, but the quality when reading leaves quite a lot to wish for, since no low-pass filters are used.

Example 1:

```
copy Louise.AIFF AUDIO:
```

plays the file 'Louise.AIFF'.

Example 2:

```
copy AUDIO:SECONDS/10/TYPE/AIFC/B/16/F/44100/C/2 sample.AIFC
```

records 10 seconds of audio and stores it in the file 'sample.AIFC' as uncompressed *IFF-AIFC*, 16 bit stereo at 44.1 kHz.

4.4 System Files

Ahi uses a set of hardware drivers for each sound card. This means that it's easy to add support for new sound cards as they appear. At the time of writing, the following sound cards are supported:

- Aura (sampling only)
- Delfina DSP
- DraCo Motion
- Paula (the built-in audio)
- Prelude
- Toccata
- Wavetools

4.4.1 The Drivers

The hardware drivers themself are located in the 'DEVS:AHI' drawer, and are named as '<name>.audio'. They are actually libraries, in spite of being located under the 'DEVS:' assign, and will be flushed out from memory when not in use and the system needs more RAM. Many of the drivers require additional files; see below. These extra files are not delivered with AHI.

`delfina.audio`
: Requires `delfina.library`.

`paula.audio`
: On startup, the file 'ENV:CyberSound/SoundDrivers/14Bit_Calibration' is read and used for the 14 bit DAC calibration. The environment variable 'AHIpaulaFilterFreq' is also checked, and should be set to a frequency in Hertz. If the mixing frequency is higher than this value, the internal low-pass filter will be turned off. If it is lower, the filter will be activated. The default is 0 Hz, which means that the filter will always be turned off. Example:

```
SetEnv AHIpaulaFilterFreq 16000
Copy ENV:AHIpaulaFilterFreq ENVARC:
```

`toccata.audio`
: Requires `toccata.library`. This driver also reads the environment variable 'AHItoccataNoTask'. If set to '1', all mixing will be done in a *Software Interrupt* which means the sound output will not suffer when multitasking is turned off. The back side is that it requires a faster CPU. Example:

```
SetEnv AHItoccataNoTask 1
Copy ENV:AHItoccataNoTask ENVARC:
```

Please note that this driver is used for both the DraCo Motion and Toccata.

`wavetools.audio`
: Requires `dad_audio.device`.

4.4.2 The Mode Descriptors

The files in 'DEVS:AudioModes' describes the available audio modes that you can chose from in the audio mode requester. All files located in this drawer will be scanned the first time AHI is used, and added to the internal mode database.

The following modes are available for most drivers:

'Mono'
: Mono output, all sounds will be centered, and no surround sound is possible.

'Stereo'
: Stereo output, but all sounds are either forces to the extreme left or extreme right—centered sounds are not possible, for example. This mode will probably use slightly more CPU power than the "mono" mode.

'Stereo++'
: Stereo output with free positioning of all sounds—an instrument can be placed anywhere between the two speakers, for example. Unless the program only uses the extremes when positioning a sound, this mode will eat more CPU cycles than the "stereo" mode.

'`Fast mono`'
'`Fast stereo`'
'`Fast stereo++`'
: "Fast" modes take some shortcuts in order to reduce the CPU usage. For 8 bit samples, multiplication tables will be used, which speeds up mixing by magnitudes and still gives the same quality with the exception of volume levels—instead of 256 levels only 32 are available. For 16 bit samples, the shortcuts are a bit more crude: the volume of each sound will be rounded to a power of 2 before it's played. This means that a 16 bit sound will only be played at volume levels of 100%, 50%, 25%, 12.5% etc. If surround sounds are played, the normal (not "fast") mixing routines will be used. You can use the preferences program (see Section 4.2.2.2 [Advanced settings], page 9) to disable surround sounds for "fast" modes.

5 The Author

The author can be reached at the following addresses:

Electronic mail
⟨lcs@lysator.liu.se⟩

Standard mail
Martin Blom
Alsättersgatan 15A:24
SE-584 35 Linköping
Sweden

World-Wide Web
'http://www.lysator.liu.se/~lcs'

5.1 The Man

Martin Blom was born 1974 in a town in Sweden called Jönköping. He had a happy childhood, lots of good friends, and a great family. He did his homework and went to church every Sunday.

But then, one cold, dark Christmas Eve in the year of our Lord 1986, everything went wrong. This was the day when *it* entered his life. At once, there were fights among the brothers. They all wanted to use *it*. Martin started to avoid playing with kids that didn't share his passion for *it*. The school work suffered. Other interests suffered. *It* was the Commodore 64 home computer, and it would forever change his life.

Today, more than ten years after the tragedy, things are worse than ever. He is studying *Computer Science and Engineering* at *Linköping Institute of Technology*, surrounded every day by other computer nerds.

Martin has spent loads of money on computers over the years: Amiga 500, Amiga 4000/040, Commodore 128D, Commodore 64 (in order of appearance), modem, monitors, disks, mice etc. Interesting enough, no sound card. He did, however, build a sound card of his own for the Commodore 64, and he likes to mention that now and then (you see, this was one of the few hardware projects that actually worked!). 4 channels, 8 bit samples. He even wrote a module player for the good old 64. And it had quadrascopes.

5.2 The Myth

Some people actually seem to believe that Martin is a good programmer. They couldn't be more wrong. He is lazy, has no patience, he is a slow thinker and he doesn't like anything he *has* to do.

Martin used to say

- If you can't write applications, write games.
- If you can't write games, write demos.
- If you can't write demos, write utilities.

- If you can't write utilities, write BBS intros and doors.
- If you can't do that either, get a modem and start trading.

And guess what? He tried demos. He tried utilities. He tried intros. He wrote a door for /X. And he traded warez.

5.3 The Concept

What do you do if you don't have the patience to write applications, if you only write moderate demos, are tired of utilities, hate BBS doors, are totally fed up with playing games and have decided to get legal and stop pirating software? Simple. Try a new concept!

Take a deep breath. Close your eyes. Think of one thing your computer lacks. Think of one of the things that makes your favorite toy feel outdated. Think of something that nobody has (successfully) tried before. Then write the software, and release it as Freeware.

In Martins case, that something was hardware independent audio.

Come on, admit it! It's brilliant. It doesn't matter if you are a good programmer. It doesn't matter if it takes 3 years to get to a half-finished product. It doesn't matter if you give it the most unimaginative name in the world—you can even use a TLA[1]. Nobody is going to say your software sucks, because nobody can say he has done better himself. Nobody is going to complain if you're slow on releasing bug fixes and updates, because the software is free. And nobody is going to be angry with you if you stop developing the software—because it sucked in the first place, remember?

This concept won't make you rich, but are rich people really happier?

[1] Three Letter Acronym

6 Acknowledgments

The author wish to give special thanks to the following persons (in alphabetical order):

Daniel Arthursson and Johan Nyblom
: For making it possible to write the first driver for a sound card, the *Wavetools* card. I'm sure AHI would not have been accepted as quick as it was without this driver. Funny that it didn't even work...

Jyrki Petsalo and Teemu Suikki
: For the Delfina driver, and for supporting AHI in the early days.

Pauli Porkka
: For active support and promotion of AHI from the beginning.

Thomas Wenzel
: For the Prelude driver.

All the rest
: Many, many other have helped me, sent suggestions etc. I owe you a lot.

And of course, the catalog translators:

Stphane Barbaray
: The Frensh translation.

Roger Hågensen
: The Norwegian translation.

Bernardo Innocenti
: The Italian translation.

Pauli Porkka
: The Finnish translation.

Michel Vissers
: The Dutch translation.

6.1 Contributors

The following people has contributed to the AHI project with code:

Johan Nyblom ⟨`nyblom@ludd.luth.se`⟩
: The latest Wavetools driver.

Pauli Porkka ⟨`pporkka@iki.fi`⟩
: The first version of the Toccata driver.

Teemu Suikki ⟨`zuikkis@zuikkis.pp.sci.fi`⟩
: The Delfina driver.

Thomas Wenzel ⟨`wenzel@unixserv.rz.fh-hannover.de`⟩
: The Prelude driver.

Concept Index

A

Acknowledgments ... 17
AddAudioModes ... 7
Advanced settings ... 9
AHI, Overview ... 1
AHI, Preferences program ... 7
AHI-Handler ... 10
AHIpaulaFilterFreq variable ... 12
AHItoccataNoTask variable ... 12
AIFC ... 11
AIFF ... 11
Audio mode settings ... 9
Audio modes, overview ... 12
AUDIO: ... 10
Aura ... 11
Author of AHI ... 15

C

Contributors ... 17
Copyright ... 3
CPU usage limit ... 10

D

Debug level ... 9
Delfina DSP ... 11
Disclaimer ... 3
Distortion, while recording ... 11
Distribution ... 3
Donations ... 5
DraCo Motion ... 11
Drivers ... 11

E

Echo, enable/disable/fast ... 9

F

Fame ... 16

I

IFF-AIFC ... 11
IFF-AIFF ... 11

J

Jesus Christ ... 15

L

Legal nonsense ... 3
License ... 3

M

Mode settings ... 9
Modules on a C64 ... 15

N

Nerd, definition of ... 15

O

Overview ... 1

P

Paula ... 11
Paula, custom chip ... 1
Preferences ... 7
Prelude ... 11

R

Recursion ... 19

S

Settings ... 7
Software license ... 3
Sound card drivers ... 11
Surround sound, enable/disable ... 9
System description ... 7
System Files ... 11

T

The Author ... 15
The Concept ... 16
The Drivers ... 12
The Man ... 15
The Mode Descriptors ... 12
The Myth ... 15
Toccata ... 11

W

Wavetools ... 11

Table of Contents

1 Overview 1

2 Distribution 3

3 Donations 5

4 System description 7

4.1 AddAudioModes 7
4.2 AHI 7
4.2.1 Menus 8
4.2.1.1 '`Project`' Menu 8
4.2.1.2 '`Edit`' Menu 8
4.2.1.3 '`Settings`' Menu 8
4.2.1.4 '`Help`' Menu 9
4.2.2 Pages 9
4.2.2.1 '`Mode settings`' Page 9
4.2.2.2 '`Advanced settings`' Page 9
4.3 AHI-Handler 10
4.4 System Files 11
4.4.1 The Drivers 12
4.4.2 The Mode Descriptors 12

5 The Author 15

5.1 The Man 15
5.2 The Myth 15
5.3 The Concept 16

6 Acknowledgments 17

6.1 Contributors 17

Concept Index 19