The Linux Kernel HOWTO

Brian Ward, bri@blah.math.tu-graz.ac.at v0.36, 10 September 1995

This is a detailed guide to kernel configuration, compilation, and upgrades.

Contents

1 Introduction **3**

1.1 Read this first! (I mean it) . . . 4

1.2 A word on style . . . 4

2 Important questions and their answers **4**

2.1 What does the kernel do, anyway? . . . 4

2.2 Why would I want to upgrade my kernel? . . . 5

2.3 What kind of hardware do the newer kernels support? . . . 5

2.4 What version of gcc and libc do I need? . . . 5

2.5 What's a loadable module? . . . 5

2.6 How much disk space do I need? . . . 5

2.7 How long does it take? . . . 5

3 How to actually configure the kernel **6**

3.1 Getting the source . . . 6

3.2 Unpacking the source . . . 6

3.3 Configuring the kernel . . . 7

3.3.1 Kernel math emulation . . . 7

3.3.2 Normal (MFM/RLL) disk and IDE disk/cdrom support . . . 7

3.3.3 Networking support . . . 7

3.3.4 Limit memory to low 16MB . . . 7

3.3.5 System V IPC . . . 8

3.3.6 Use -m486 flag for 486-specific optimizations . . . 8

3.3.7 SCSI support . . . 8

3.3.8 Network device support . . . 8

3.3.9 Filesystems . . . 8

3.3.10 Character devices . . . 9
3.3.11 Sound card . . . 9
3.3.12 Other configuration options . . . 10
3.3.13 Kernel hacking . . . 10
3.4 Now what? (The Makefile) . . . 10

4 Compiling the kernel **10**
4.1 Cleaning and depending . . . 10
4.2 Compile time . . . 10
4.3 Other "make"ables . . . 11
4.4 Installing the kernel . . . 11

5 Patching the kernel **12**
5.1 Applying a patch . . . 12
5.2 If something goes wrong . . . 12
5.3 Getting rid of the .orig files . . . 13
5.4 Other patches . . . 13

6 Additional packages **14**
6.1 kbd . . . 14
6.2 util-linux . . . 14
6.3 hdparm . . . 14

7 Some pitfalls **14**
7.1 make clean . . . 14
7.2 Huge or slow kernels . . . 14
7.3 Kernel doesn't compile . . . 15
7.4 New version of the kernel doesn't seem to boot . . . 15
7.5 You forgot to run LILO, or system doesn't boot at all . . . 15
7.6 It says 'warning: bdflush not running' . . . 16
7.7 It says weird things about obsolete routing requests . . . 16
7.8 Firewalling not working in 1.2.0 . . . 16
7.9 "Not a compressed kernel Image file" . . . 17
7.10 Problems with console terminal after upgrade to 1.3.x . . . 17

7.11 Can't seem to compile things after kernel upgrade 17

8 Modules **17**

8.1 Installing the module utilities 17

8.2 Modules distributed with the kernel 18

9 Other configuration options **18**

9.1 General setup 18

9.2 Networking options 19

10 Tips and tricks **19**

10.1 Redirecting output of the make or patch commands 19

10.2 Conditional kernel install 19

10.3 Kernel updates 20

11 Misc **20**

11.1 Author 20

11.2 To do 20

11.3 Contributions 21

11.4 Copyright notice, License, and all that stuff 21

1 Introduction

This is release 0.35 of the Kernel-HOWTO. Should you read this document? Well, see if you've got any of the following symptoms:

- "Arg! This wizzo-46.5.6 package says it needs kernel release 1.1.193 and I still only have release 1.0.9!"
- There's a device driver in one of the newer kernels that you just gotta have
- You really have no idea at all how to compile a kernel
- "Is this stuff in the README *really* the whole story?"
- You came, you tried, it didn't work
- You know how to compile and install a kernel, and people seem to know this. Therefore, they keep whining to you to help them install their kernels.

1.1 Read this first! (I mean it)

Some of the examples in this document assume that you have GNU `tar`, `find`, and `xargs`. These are quite standard; this should not cause problems. It is also assumed that you know your system's filesystem structure; if you don't, it is critical that you keep a written copy of the `mount` command's output during normal system operation (or a listing of `/etc/fstab`, if you can read it). This information is important, and does not change unless you repartition your disk, add a new one, reinstall your system, or something similar.

The latest "production" kernel version at the time of this writing was 1.2.13, meaning that the references and examples correspond to that release. Even though I try to make this document as version-independent as possible, the kernel is constantly under development, so if you get a newer release, it will inevitably have some differences. Again, this should not cause major problems, but it may create some confusion.

There are two versions of the linux kernel source, "production" and "development." Production releases started with 1.0.x and and are currently the even-numbered releases; 1.0.x was production, 1.2.x is production, and 1.4.x is expected to be the same. These kernels are considered to be the most stable, bug-free versions available at the time of release. The development kernels (1.1.x, 1.3.x, etc) are meant as testing kernels, for people willing to test out new and possibly very buggy kernels. You have been warned.

1.2 A word on style

`Text that looks like this` is either something that appears on your screen, a filename, or something that can be directly typed in, such as a command, or options to a command (if you're looking at a plain-text file, it doesn't look any different). Commands and other input are frequently quoted (with ` '), which causes the following classic punctuation problem: if such an item appears at the end of a sentence in quotes, people often type a '.' along with the command, because the American quoting style says to put the period inside of the quotation marks. Even though common sense should tell one to strip off the punctuation first, many people simply do not remember, so I will place it outside the quotation marks in such cases. For example, I would write '`make config`', not '`make config.`'

2 Important questions and their answers

2.1 What does the kernel do, anyway?

The Unix kernel acts as a mediator for your programs. First, it does the memory management for all of the running programs (processes), and makes sure that they all get a fair (or unfair, if you please) share of the processor's cycles. In addition, it provides a nice, fairly portable interface for programs to talk to your hardware.

There is certainly more to the kernel's operation than this, but these basic functions are the most important to know.

2.2 Why would I want to upgrade my kernel?

Newer kernels generally offer the ability to talk to more types of hardware (that is, they have more device drivers), they can have better process management, they can run faster than the older versions, they could be more stable than the older versions, and they fix silly bugs in the older versions. Most people upgrade kernels because they want the device drivers and the bug fixes.

2.3 What kind of hardware do the newer kernels support?

See the Hardware-HOWTO. Alternatively, you can look at the '`config.in`' file in the linux source, or just find out when you try '`make config`'. This shows you all hardware supported by the standard kernel distribution, but not everything that linux supports; many common device drivers (such as the PCMCIA drivers and some tape drivers) are loadable modules maintained and distributed separately.

2.4 What version of gcc and libc do I need?

Linus recommends a version of gcc in the `README` file included with the linux source. If you don't have this version, the documentation in the recommended version of gcc should tell you if you need to upgrade your libc. This is not a difficult procedure, but it is important to follow the instructions.

2.5 What's a loadable module?

These are pieces of kernel code which are not linked (included) directly in the kernel. One compiles them separately, and can insert and remove them into the running kernel at almost any time. Due to its flexibility, this is now the preferred way to code certain kernel features. Many popular device drivers, such as the PCMCIA drivers and the QIC-80/40 tape driver, are loadable modules.

2.6 How much disk space do I need?

It depends on your particular system configuration. First, the compressed linux source is 2.35 megabytes large at version 1.2.0. Most keep this even after unpacking. Uncompressed, it takes up 10 MB. But that's not the end – you need more to actually compile the thing. This depends on how much you configure into your kernel. For example, on my 386, I have networking, the 3Com 3C503 driver, and five filesystems configured, using 18 MB. Adding the compressed linux source, you need about 20 MB for this particular configuration. On another system, without network device support (but still with networking support), and sound card support, it consumes 14 MB. Also, a newer kernel is certain to have a larger source tree than an older one, so, in general, if you have a lot of hardware, make sure that you have a big enough hard disk in that mess.

2.7 How long does it take?

For most people, the answer is "fairly long." The speed of your system and the amount of memory you have ultimately determines the time, but there is a small bit to do with the amount of stuff you configure into the

kernel. On a 486DX4/100 with 16 MB of RAM, on a kernel with five filesystems, networking support, and sound card drivers, it takes around 20 minutes. On a 386DX/40 (8 MB RAM) with a similar configuration, compilation lasts nearly 1.5 hours. It is a generally good recommendation to make a little coffee, watch some TV, knit, or whatever you do for fun while your machine compiles the kernel. You can have someone else with a faster machine compile it for you if you really have a slow machine.

3 How to actually configure the kernel

3.1 Getting the source

You can obtain the source via anonymous ftp from `ftp.funet.fi` in `/pub/OS/Linux/PEOPLE/Linus`, a mirror, or other sites. It is typically labelled `linux-x.y.z.tar.gz`, where `x.y.z` is the version number. Newer (better?) versions and the patches are typically in subdirectories such as '`v1.1`' and '`v1.2`' The highest number is the latest version, and is usually a "test release," meaning that if you feel uneasy about beta or alpha releases, you should stay with a major release.

I *strongly* suggest that you use a mirror ftp site instead of ftp.funet.fi. Here is a short list of mirrors and other sites:

```
USA:            tsx-11.mit.edu:/pub/linux/sources/system
USA:            sunsite.unc.edu:/pub/Linux/kernel
UK:             src.doc.ic.ac.uk:/pub/Linux/kernel (?)
Austria:        fvkma.tu-graz.ac.at:/pub/linux/linus
Germany:        ftp.Germany.EU.net:/pub/os/Linux/Local.EUnet/Kernel/Linus
Germany:        ftp.dfv.rwth-aachen.de:/pub/linux/kernel
France:         ftp.ibp.fr:/pub/linux/sources/system/patches
Australia:      kirk.bond.edu.au:/pub/OS/Linux/kernel
```

If you do not have ftp access, a list of BBS systems which carry linux is posted periodically to comp.os.linux.announce; try to obtain this.

3.2 Unpacking the source

Log in as or `su` to '`root`', and `cd` to `/usr/src`. If you installed kernel source when you first installed linux (as most do), there will already be a directory called '`linux`' there, which contains the entire old source tree. If you have the disk space and you want to play it safe, preserve that directory. A good idea is to figure out what version your system runs now and rename the directory accordingly. The command '`uname -r`' prints the current kernel version. Therefore, if '`uname -r`' said '`1.0.9`', you would rename (with '`mv`') '`linux`' to '`linux-1.0.9`'. If you feel mildly reckless, just wipe out the entire directory. In any case, make certain there is no '`linux`' directory in `/usr/src` before unpacking the full source code.

Now, in `/usr/src`, unpack the source with '`tar zxpvf linux-x.y.z.tar.gz`' (if you've just got a `.tar` file with no `.gz` at the end, '`tar xpvf linux-x.y.z.tar`' works.). The contents of the source will fly by. When finished, there will be a new '`linux`' directory in `/usr/src`. `cd` to `linux` and look over the `README` file. There

will be a section with the label '`INSTALLING the kernel`'. Carry out the instructions when appropriate – symbolic links that should be in place, removal of stale `.o` files, etc.

3.3 Configuring the kernel

Note: Some of this is reiteration/clarification of a similar section in Linus' `README` file.

The command '`make config`' while in `/usr/src/linux` starts a configure script which asks you many questions. It requires bash, so verify that bash is `/bin/bash`, `/bin/sh`, or `$BASH`.

You are ready to answer the questions, usually with '`y`' (yes) or '`n`' (no). Some of the more obvious and non-critical options are not described here; see the section "Other configuration options" for short descriptions of a few others.

3.3.1 Kernel math emulation

If you don't have a math coprocessor (you have a bare 386 or 486SX), you must say '`y`' to this. If you do have a coprocessor and you still say '`y`', don't worry too much – the coprocessor is still used and the emulation ignored. The only consequence is that the kernel will be larger (costing RAM).

3.3.2 Normal (MFM/RLL) disk and IDE disk/cdrom support

You probably need to support this; it means that the kernel will support standard PC hard disks, which most people have. This driver does not include SCSI drives; they come later in the configuration.

You will then be asked about the "old disk-only" and "new IDE" drivers. You want to choose one of them; the main difference is that the old driver only supports two disks on a single interface, and the new one supports a secondary interface and IDE/ATAPI cdrom drives. The new driver is 4k larger than the old one and is also supposedly "improved," meaning that aside from containing a different number of bugs, it might improve your disk performance, especially if you have newer hardware.

3.3.3 Networking support

In principle, you would only say '`y`' if your machine is on a network such as the internet, or you want to use SLIP, PPP, term, etc to dial up for internet access. However, as many packages (such as the X window system) require networking support even if your machine does not live on a real network, you should say '`y`'. Later on, you will be asked if you want to support TCP/IP networking; again, say '`y`' here if you are not absolutely sure.

3.3.4 Limit memory to low 16MB

There exist buggy 386 DMA controllers which have problems with addressing anything more than 16 MB of RAM; you want to say '`y`' in the (rare) case that you have one.

3.3.5 System V IPC

One of the best definitions of IPC (Interprocess Communication) is in the Perl book's glossary. Not surprisingly, Perl employs it to let processes talk to each other, as well as many other packages, so it is not a good idea to say `n` unless you know exactly what you are doing.

3.3.6 Use -m486 flag for 486-specific optimizations

This optimizes the kernel for use on a 486 processor. The new kernel will be slightly larger, but will work fine on a 386.

3.3.7 SCSI support

If you have a SCSI device, say '`y`'. You will be prompted for further information, such as support for CD-ROM, disks, and what kind of SCSI adapter you have. See the SCSI-HOWTO for greater detail.

3.3.8 Network device support

If you have a network card, or you would like to use SLIP, PPP, or a parallel port adapter, say '`y`'. The config script will prompt for which kind of card you have, and which protocol to use.

3.3.9 Filesystems

The configure script then asks if you wish to support the following filesystems:

Standard (minix) - Newer distributions don't create minix filesystems, and many people don't use it, but it may still be a good idea to configure this one. Some "rescue disk" programs use it, and still more floppies may have a minix filesystem, since the minix filesystem is less painful to use on a floppy.

Extended fs - This was the first version of the extended filesystem, which is no longer in widespread use. Chances are that you'll know it if you need it.

Second extended - This is widely used in new distributions. You probably have one of these, and need to say '`y`'.

xiafs filesystem - At one time, this was not uncommon, but at the time of this writing, I did not know of anyone using it.

msdos - If you want to use your MS-DOS hard disk partitions, or mount MS-DOS formatted floppy disks, say '`y`'.

umsdos - This filesystem expands an MS-DOS filesystem with usual Unix-like features such as long filenames. It is not useful for people (like me) who "don't do DOS."

/proc - Another one of the greatest things since powdered milk (idea shamelessly stolen from Bell Labs, I guess). One doesn't make a proc filesystem on a disk; this is a filesystem interface to the kernel and processes. Many process listers (such as '`ps`') use it. Try '`cat /proc/meminfo`' or '`cat /proc/devices`'

sometime. Some shells (rc, in particular) use `/proc/self/fd` (known as `/dev/fd` on other systems) for I/O. You should almost certainly say '`y`' to this; many important linux tools depend on it.

NFS - If your machine lives on a network and you want to use filesystems which reside on other systems with NFS, say '`y`'.

ISO9660 - Found on most CD-ROMs.

OS/2 HPFS - At the time of this writing, a read-only fs for OS/2 HPFS.

System V and Coherent - for partitions of System V and Coherent systems (These are other PC Unix variants).

But I don't know which filesystems I need! Ok, type '`mount`'. The output will look something like this:

```
blah# mount
/dev/hda1 on / type ext2 (defaults)
/dev/hda3 on /usr type ext2 (defaults)
none on /proc type proc (defaults)
/dev/fd0 on /mnt type msdos (defaults)
```

Look at each line; the word next to '`type`' is the filesystem type. In this example, my `/` and `/usr` filesystems are second extended, I'm using `/proc`, and there's a floppy disk mounted using the msdos (bleah) filesystem.

You can try '`cat /proc/filesystems`' if you have `/proc` currently enabled; it will list your current kernel's filesystems.

The configuration of rarely-used, non-critical filesystems can cause kernel bloat; see the section on modules for a way to avoid this.

3.3.10 Character devices

Here, you enable the drivers for your printer, busmouse, PS/2 mouse (many notebooks use the PS/2 mouse protocol for their built-in trackballs), some tape drives, and other such "character" devices. Say '`y`' when appropriate.

Note: Selection is a program which allows the use of the mouse outside of the X window system for cut and paste between virtual consoles. It's fairly nice if you have a serial mouse, because it coexists well with X, but you need to do special tricks for others. Selection support was a configuration option at one time, but is now standard.

3.3.11 Sound card

If you feel a great desire to hear `biff` bark, say '`y`', and later on, another config program will compile and ask you all about your sound board. (A note on sound card configuration: when it asks you if you want to install the full version of the driver, you can say '`n`' and save some kernel memory by picking only the features which you deem necessary.)

3.3.12 Other configuration options

Not all of the configuration options are listed here because they change too often or fairly self-evident (for instance, 3Com 3C509 support). There exists a fairly comprehensive list of all the options (plus a way to place them into the `Configure` script) put together by Axel Boldt (`axel@uni-paderborn.de`) with the following URL:

`http://math-www.uni-paderborn.de/~axel/config_help.html`

or via anonymous FTP at:

`ftp://sunsite.unc.edu/pub/Linux/kernel/config/krnl_cnfg_hlp.x.yz.tgz`

where the `x.yz` is the version number.

3.3.13 Kernel hacking

¿From Linus' README:

the "kernel hacking" configuration details usually result in a bigger or slower kernel (or both), and can even make the kernel less stable by configuring some routines to actively try to break bad code to find kernel problems (kmalloc()). Thus you should probably answer 'n' to the questions for a "production" kernel.

3.4 Now what? (The Makefile)

After you `make config`, a message tells you that your kernel has been configured, and to "check the top-level `Makefile` for additional configuration," etc.

So, look at the `Makefile`. You probably will not need to change it, but it never hurts to look. You can also change its options with the '`rdev`' command once the new kernel is in place.

4 Compiling the kernel

4.1 Cleaning and depending

When the configure script ends, it also tells you to '`make dep`' and '`clean`'. So, do the '`make dep`'. This insures that all of the dependencies, such the include files, are in place. It does not take long, unless your computer is fairly slow to begin with. When finished, do a '`make clean`'. This removes all of the object files and some other things that an old version leaves behind. *Don't* forget this step.

4.2 Compile time

After `dep`ending and `clean`ing, you may now '`make zImage`' or '`make zdisk`' (This is the part that takes a long time.) '`make zImage`' will compile the kernel, and leave a file in `arch/i386/boot` called '`zImage`'

(among other things). This is the new compressed kernel. '`make zdisk`' does the same thing, but also places the new `zImage` on a floppy disk which you hopefully put in drive "A:". '`zdisk`' is fairly handy for testing new kernels; if it bombs (or just doesn't work right), just remove the floppy and boot with your old kernel. It can also be a handy way to boot if you accidentally remove your kernel (or something equally as dreadful). You can also use it to install new systems when you just dump the contents of one disk onto the other ("all this and more! NOW how much would you pay?").

All reasonably recent kernels are compressed, hence the '`z`' in front of the names. A compressed kernel automatically decompresses itself when executed.

4.3 Other "make"ables

'`make mrproper`' will do a more extensive '`clean`'ing. It is sometimes necessary; you may wish to do it at every patch. See the section on modules for a description of '`make modules`'.

4.4 Installing the kernel

After you have a new kernel that seems to work the way you want it to, it's time to install it. Most people use LILO (Linux Loader) for this. '`make zlilo`' will install the kernel, run LILO on it, and get you all ready to boot, BUT ONLY if lilo is configured in the following way on your system: kernel is `/vmlinuz`, lilo is in `/sbin`, and your lilo config (`/etc/lilo.conf`) agrees with this.

Otherwise, you need to use LILO directly. It's a fairly easy package to install and work with, but it has a tendency to confuse people with the configuration file. Look at the config file (either `/etc/lilo/config` for older versions or `/etc/lilo.conf` for new versions), and see what the current setup is. The config file looks like this:

```
image = /vmlinuz
    label = Linux
    root = /dev/hda1
    ...
```

The '`image =`' is set to the currently installed kernel. Most people use `/vmlinuz`. '`label`' is used by lilo to determine which kernel or operating system to boot, and '`root`' is the `/` of that particular operating system. Make a backup copy of your old kernel and copy the `zImage` which you just made into place (you would say '`cp zImage /vmlinuz`' if you use '`/vmlinuz`'). Then, rerun lilo – on newer systems, you can just run '`lilo`', but on older stuff, you might have to do an `/etc/lilo/install` or even an `/etc/lilo/lilo -C /etc/lilo/config`.

If you would like to know more about LILO's configuration, or you don't have LILO, get the newest version from your favorite ftp site and follow the instructions.

To boot one of your old kernels off the hard disk (another way to save yourself in case you screw up the new kernel), copy the lines below (and including) '`image = xxx`' in the LILO config file to the bottom of the file, and change the '`image = xxx`' to '`image = yyy`', where '`yyy`' is the full pathname of the file you saved your backup kernel to. Then, change the '`label = zzz`' to '`label = linux-backup`' and rerun `lilo`. You may

need to put a line in the config file saying '`delay=x`', where x is an amount in tenths of a second, which tells LILO to wait that much time before booting, so that you can interrupt it (with the shift key, for example), and type in the label of the backup boot image (in case unpleasant things happen).

5 Patching the kernel

5.1 Applying a patch

Incremental upgrades of the kernel are distributed as patches. For example, if you have version 1.1.45, and you notice that there's a '`patch46.gz`' out there for it, it means you can upgrade to version 1.1.46 through application of the patch. You might want to make a backup of the source tree first ('`make clean`' and then '`cd /usr/src; tar zcvf old-tree.tar.gz linux`' will make a compressed tar archive for you.).

So, continuing with the example above, let's suppose that you have '`patch46.gz`' in `/usr/src`. `cd` to `/usr/src` and do a '`zcat patch46.gz | patch -p0`' (or '`patch -p0 < patch46`' if the patch isn't compressed). You'll see things whizz by (or flutter by, if your system is that slow) telling you that it is trying to apply hunks, and whether it succeeds or not. Usually, this action goes by too quickly for you to read, and you're not too sure whether it worked or not, so you might want to use the `-s` flag to `patch`, which tells `patch` to only report error messages (you don't get as much of the "hey, my computer is actually doing something for a change!" feeling, but you may prefer this..). To look for parts which might not have gone smoothly, cd to `/usr/src/linux` and look for files with a `.rej` extension. Some versions of `patch` (older versions which may have been compiled with on an inferior filesystem) leave the rejects with a `#` extension. You can use '`find`' to look for you;

```
find .  -name '*.rej' -print
```

prints all files who live in the current directory or any subdirectories with a `.rej` extension to the standard output.

If everything went right, do a '`make clean`', '`config`', and '`dep`' as described in sections 3 and 4.

There are quite a few options to the `patch` command. As mentioned above, `patch -s` will suppress all messages except the errors. If you keep your kernel source in some other place than `/usr/src/linux`, `patch -p1` (in that directory) will patch things cleanly. Other `patch` options are well-documented in the manual page.

5.2 If something goes wrong

The most frequent problem that used to arise was when a patch modified a file called '`config.in`' and it didn't look quite right, because you changed the options to suit your machine. This has been taken care of, but one still might encounter it with an older release. To fix it, look at the `config.in.rej` file, and see what remains of the original patch. The changes will typically be marked with '`+`' and '`-`' at the beginning of the line. Look at the lines surrounding it, and remember if they were set to '`y`' or '`n`'. Now, edit `config.in`, and change '`y`' to '`n`' and '`n`' to '`y`' when appropriate. Do a

```
patch -p0 < config.in.rej
```

and if it reports that it succeeded (no fails), then you can continue on with a configuration and compilation. The `config.in.rej` file will remain, but you can get delete it.

If you encounter further problems, you might have installed a patch out of order. If patch says '`previously applied patch detected: Assume -R?`', you are probably trying to apply a patch which is below your current version number; if you answer '`y`', it will attempt to degrade your source, and will most likely fail; thus, you will need to get a whole new source tree (which might not have been such a bad idea in the first place).

To back out (unapply) a patch, use '`patch -R`' on the original patch.

The best thing to do when patches really turn out wrong is to start over again with a clean, out-of-the-box source tree (for example, from one of the `linux-x.y.z.tar.gz` files), and start again.

5.3 Getting rid of the .orig files

After just a few patches, the `.orig` files will start to pile up. For example, one 1.1.51 tree I had was once last cleaned out at 1.1.48. Removing the .orig files saved over a half a meg.

```
find .  -name '*.orig' -exec rm -f {} ';'
```

will take care of it for you. Versions of `patch` which use `#` for rejects use a tilde instead of `.orig`.

There are better ways to get rid of the `.orig` files, which depend on GNU `xargs`:

```
find .  -name '*.orig' | xargs rm
```

or the "quite secure but a little more verbose" method:

```
find . -name '*.orig' -print0 | xargs --null rm --
```

5.4 Other patches

There are other patches (I'll call them "nonstandard") than the ones Linus distributes. If you apply these, Linus' patches may not work correctly and you'll have to either back them out, fix the source or the patch, install a new source tree, or a combination of the above. This can become very frustrating, so if you do not want to modify the source (with the possibility of a very bad outcome), back out the nonstandard patches before applying Linus', or just install a new tree. Then, you can see if the nonstandard patches still work. If they don't, you are either stuck with an old kernel, playing with the patch or source to get it to work, or waiting (possibly begging) for a new version of the patch to come out.

How common are the patches not in the standard distribution? You will probably hear of them. I use the noblink patch for my virtual consoles because I hate blinking cursors (This patch is frequently updated for new kernel releases.).

6 Additional packages

Your linux kernel has many features which are not explained in the kernel source itself; these features are typically utilized through external packages. Some of the most common are listed here.

6.1 kbd

The linux console probably has more features than it deserves. Among these are the ability to switch fonts, remap your keyboard, switch video modes (in newer kernels), etc. The kbd package has programs which allow the user to do all of this, plus many fonts and keyboard maps for almost any keyboard, and is available from the same sites that carry the kernel source.

6.2 util-linux

Rik Faith (`faith@cs.unc.edu`) keeps a large collection of linux utilities which are, by odd coincidence, called util-linux. Available via anonymous ftp from sunsite.unc.edu in `/pub/Linux/system/Misc`, it contains programs such as `setterm`, `rdev`, and `ctrlaltdel`, which are relevant to the kernel. As Rik says, *do not install without thinking;* you do not need to install everything in the package, and it could very well cause serious problems if you do.

6.3 hdparm

As with many packages, this was once a kernel patch and support programs. The patches made it into the official kernel, and the programs to optimize and play with your hard disk are distributed separately.

7 Some pitfalls

7.1 make clean

If your new kernel does really weird things after a routine kernel upgrade, chances are you forgot to `make clean` before compiling the new kernel. Symptoms can be anything from your system outright crashing, strange I/O problems, to crummy performance. Make sure you do a `make dep`, too.

7.2 Huge or slow kernels

If your kernel is sucking up a lot of memory, is too large, or just takes forever to compile even when you've got your new 486DX6/440 working on it, you've probably got lots of unneeded stuff (device drivers, filesystems, etc) configured. If you don't use it, don't configure it, because it does take up memory. The most obvious symptom of kernel bloat is extreme swapping in and out of memory to disk; if your disk is making a lot of noise, look over your kernel configuration.

You can find out how much memory the kernel is using by taking the total amount of memory in your machine and subtracting it from the amount of "total mem" in `/proc/meminfo` or the output of the command '`free`'. You can also find out by doing a '`dmesg`' (or by looking at the kernel log file, wherever it is on your system). There will be a line which looks like this:

```
Memory:  15124k/16384k available (552k kernel code, 384k reserved, 324k data)
```

My 386 (which has slightly less junk configured) says this:

```
Memory:  7000k/8192k available (496k kernel code, 384k reserved, 312k data)
```

7.3 Kernel doesn't compile

If it does not compile, then it is likely that a patch failed, or your source is somehow corrupt. Your version of gcc also might not be correct, or could also be corrupt (for example, the include files might be in error). Make sure that the symbolic links which Linus describes in the `README` are set up correctly. In general, if a standard kernel does not compile, something is seriously wrong with the system, and reinstallation of certain tools is probably necessary.

7.4 New version of the kernel doesn't seem to boot

You did not run LILO, or it is not configured correctly. One thing that "got" me once was a problem in the config file; it said '`boot = /dev/hda1`' instead of '`boot = /dev/hda`' (This can be really annoying at first, but once you have a working config file, you shouldn't need to change it.).

7.5 You forgot to run LILO, or system doesn't boot at all

Ooops! The best thing you can do here is to boot off of a floppy disk and prepare another bootable floppy (such as '`make zdisk`' would do). You need to know where your root (`/`) filesystem is and what type it is (e.g. second extended, minix). In the example below, you also need to know what filesystem your `/usr/src/linux` source tree is on, its type, and where it is normally mounted.

In the following example, `/` is `/dev/hda1`, and the filesystem which holds `/usr/src/linux` is `/dev/hda3`, normally mounted at `/usr`. Both are second extended filesystems. The working kernel image in `/usr/src/linux/arch/i386/boot` is called `zImage`.

The idea is that if there is a functioning `zImage`, it is possible to use that for the new floppy. Another alternative, which may or may not work better (it depends on the particular method in which you messed up your system) is discussed after the example.

First, boot from a boot/root disk combo or rescue disk, and mount the filesystem which contains the working kernel image:

```
mkdir /mnt
mount -t ext2 /dev/hda3 /mnt
```

If `mkdir` tells you that the directory already exists, just ignore it. Now, `cd` to the place where the working kernel image was. Note that

```
/mnt + /usr/src/linux/arch/i386/boot - /usr = /mnt/src/linux/arch/i386/boot
```

Place a formatted disk in drive "A:" (not your boot or root disk!), dump the image to the disk, and configure it for your root filesystem:

```
cd /mnt/src/linux/arch/i386/boot
dd if=zImage of=/dev/fd0
rdev /dev/fd0 /dev/hda1
```

`cd` to `/` and unmount the normal `/usr` filesystem:

```
cd /
umount /mnt
```

You should now be able to reboot your system as normal from this floppy. Don't forget to run lilo (or whatever it was that you did wrong) after the reboot!

As mentioned above, there is another common alternative. If you happened to have a working kernel image in `/` (`/vmlinuz` for example), you can use that for a boot disk. Supposing all of the above conditions, and that my kernel image is `/vmlinuz`, just make these alterations to the example above: change `/dev/hda3` to `/dev/hda1` (the `/` filesystem), `/mnt/src/linux` to `/mnt`, and `if=zImage` to `if=vmlinuz`. The note explaining how to derive `/mnt/src/linux` may be ignored.

7.6 It says 'warning: bdflush not running'

This can be a severe problem. Starting with a kernel release after 1.0 (around 20 Apr 1994), a program called '`update`' which periodically flushes out the filesystem buffers, was upgraded/replaced. Get the sources to '`bdflush`' (you should find it where you got your kernel source), and install it (you probably want to run your system under the old kernel while doing this). It installs itself as '`update`' and after a reboot, the new kernel should no longer complain.

7.7 It says weird things about obsolete routing requests

Get new versions of the `route` program and any other programs which do route manipulation. `/usr/include/linux/route.h` (which is actually a file in `/usr/src/linux`) has changed.

7.8 Firewalling not working in 1.2.0

Upgrade to at least version 1.2.1.

7.9 "Not a compressed kernel Image file"

Don't use the `vmlinux` file created in `/usr/src/linux` as your boot image; `[..]/arch/i386/boot/zImage` is the right one.

7.10 Problems with console terminal after upgrade to 1.3.x

Change the word `dumb` to `linux` in the console termcap entry in `/etc/termcap`.

7.11 Can't seem to compile things after kernel upgrade

The linux kernel source includes a number of include files (the things that end with `.h`) which are referenced by the standard ones in `/usr/include`. They are typically referenced like this (where `xyzzy.h` would be something in `/usr/include/linux`):

```
#include <linux/xyzzy.h>
```

Normally, there is a link called `linux` in `/usr/include` to the `include/linux` directory of your kernel source (`/usr/src/linux/include/linux` in the typical system). If this link is not there, or points to the wrong place, most things will not compile at all. If you decided that the kernel source was taking too much room on the disk and deleted it, this will obviously be a problem. Another way it might go wrong is with file permissions; if your `root` has a umask which doesn't by allow other users to see its files by default, and you extracted the kernel source without the `p` (preserve filemodes) option, those users also won't be able to use the C compiler. Although you could use the `chmod` command to fix this, it is probably easier to re-extract the include files. You can do this the same way you did the whole source at the beginning, only with an additional argument:

```
blah# tar zxvpf linux.x.y.z.tar.gz linux/include
```

Note: "`make config`" will recreate the `/usr/src/linux` link if it isn't there.

8 Modules

Loadable kernel modules can save memory and ease configuration. The scope of modules has grown to include filesystems, ethernet card drivers, tape drivers, printer drivers, and more.

8.1 Installing the module utilities

The module utilities are available from wherever you got your kernel source as `modules-x.y.z.tar.gz`; choose the highest patchlevel `x.y.z` that is equal to or below that of your current kernel. Unpack it with '`tar zxvf modules-x.y.z.tar.gz`', `cd` to the directory it creates (`modules-x.y.z`), look over the `README`, and carry out its installation instructions (which is usually something simple, such as `make install`). You

should now have the programs `insmod`, `rmmod`, `ksyms`, `lsmod`, `genksyms`, `modprobe`, and `depmod` in `/sbin`. If you wish, test out the utilities with the "hw" example driver in `insmod`; look over the `INSTALL` file in that subdirectory for details.

`insmod` inserts a module into the running kernel. Modules usually have a `.o` extension; the example driver mentioned above is called `drv_hello.o`, so to insert this, one would say '`insmod drv_hello.o`'. To see the modules that the kernel is currently using, use `lsmod`. The output looks like this:

```
blah# lsmod
Module:         #pages:  Used by:
drv_hello           1
```

'`drv_hello`' is the name of the module, it uses one page (4k) of memory, and no other kernel modules depend on it at the moment. To remove this module, use '`rmmod drv_hello`'. Note that `rmmod` wants a *module name,* not a filename; you get this from `lsmod`'s listing. The other module utilities' purposes are documented in their manual pages.

8.2 Modules distributed with the kernel

As of version 1.2.2, many filesystems, a few SCSI drivers, several ethernet adapter drivers, and other odds and ends are loadable as modules. To use them, first make sure that you don't configure them into the regular kernel; that is, don't say `y` to it during '`make config`'. Compile a new kernel and reboot with it. Then, `cd` to `/usr/src/linux` again, and do a '`make modules`'. This compiles all of the modules which you did not specify in the kernel configuration, and places links to them in `/usr/src/linux/modules`. You can use them straight from that directory or execute '`make modules_install`', which installs them in `/lib/modules/x.y.z`, where `x.y.z` is the kernel release.

This can be especially handy with filesystems. You may not use the minix or msdos filesystems frequently. For example, if I encountered an msdos (shudder) floppy, I would `insmod /usr/src/linux/modules/msdos.o`, and then `rmmod msdos` when finished. This procedure saves about 50k of RAM in the kernel during normal operation. A small note is in order for the minix filesystem: you should *always* configure it directly into the kernel for use in "rescue" disks.

9 Other configuration options

This section contains descriptions of selected kernel configuration options (in `make config`) which are not listed in the configuration section. Most device drivers are not listed here.

9.1 General setup

`Normal floppy`
`disk support` - is exactly that. You may wish to read over the file `drivers/block/README.fd`; this is especially important for IBM Thinkpad users.

`XT harddisk support` - if you want to use that 8 bit XT controller collecting dust in the corner.

`PCI bios support` - if you have PCI, you may want to give this a shot; be careful, though, as some old PCI motherboards could crash with this option. More information about the PCI bus under linux is found in the PCI-HOWTO.

`Kernel support for ELF binaries` - ELF is an effort to allow binaries to span architectures and operating systems; linux seems to be headed in that direction.

`Set version information on all symbols for modules` - in the past, kernel modules were recompiled along with every new kernel. If you say `y`, it will be possible to use modules compiled under a different patchlevel. Read `README.modules` for more details.

9.2 Networking options

Networking options are described in the NET-2-HOWTO.

10 Tips and tricks

10.1 Redirecting output of the make or patch commands

If you would like logs of what those '`make`' or '`patch`' commands did, you can redirect output to a file. First, find out what shell you're running: '`grep root /etc/passwd`' and look for something like '`/bin/csh`'.

If you use sh or bash,

```
(command) 2>&1 | tee (output file)
```

will place a copy of `(command)`'s output in the file '`(output file)`'.

For csh or tcsh, use

```
(command) |& tee (output file)
```

For rc (Note: you probably do not use rc) it's

```
(command) >[2=1] | tee (output file)
```

10.2 Conditional kernel install

Other than using floppy disks, there are several methods of testing out a new kernel without touching the old one. Unlike many other Unix flavors, LILO has the ability to boot a kernel from anywhere on the disk (if you have a large (500 MB or above) disk, please read over the LILO documentation on how this may cause problems). So, if you add something similar to

```
image = /usr/src/linux/arch/i386/zImage
    label = new_kernel
```

to the end of your LILO configuration file, you can choose to run a newly compiled kernel without touching your old `/vmlinuz` (after running `lilo`, of course). The easiest way to tell LILO to boot a new kernel is to press the shift key at bootup time (when it says `LILO` on the screen, and nothing else), which gives you a prompt. At this point, you can enter '`new_kernel`' to boot the new kernel.

If you wish to keep several different kernel source trees on your system at the same time (this can take up a *lot* of disk space; be careful), the most common way is to name them `/usr/src/linux-x.y.z`, where `x.y.z` is the kernel version. You can then "select" a source tree with a symbolic link; for example, '`ln -sf linux-1.2.2 /usr/src/linux`' would make the 1.2.2 tree current. Before creating a symbolic link like this, make certain that the last argument to `ln` is not a real directory (old symbolic links are fine); the result will not be what you expect.

10.3 Kernel updates

Russell Nelson (`nelson@crynwr.com`) summarizes the changes in new kernel releases. These are short, and you might like to look at them before an upgrade. They are available with anonymous ftp from `ftp.emlist.com` in `pub/kchanges` or through the URL

```
http://www.crynwr.com/kchanges
```

11 Misc

11.1 Author

The author and maintainer of the Linux Kernel-HOWTO is Brian Ward (`bri@blah.math.tu-graz.ac.at`). Please send me any comments, additions, corrections, or computers. Corrections are, in particular, the most important to me. You can look at my 'home page' at one of these URLs:

```
http://www.math.psu.edu/ward/
http://blah.math.tu-graz.ac.at/~bri/
```

Even though I try to be attentive as possible with mail, please remember that I get a *lot* of mail per day, so it may take a little time to get back to you. Especially when emailing me with a question, please try extra hard to be clear and detailed in your message. I don't care if you ask simple questions; remember, if you don't ask, you may never get an answer! I'd like to thank everyone who has given me feedback.

I get a lot of mail about thing which are actually hardware problems. That's OK.

Version -0.1 was written on October 3, 1994; this document is available in SGML, PostScript, TeX, roff, and plain-text formats.

11.2 To do

The "Tips and tricks" section is a little small. I hope to expand on it with suggestions from others.

So is "Additional packages."

More debugging/crash recovery info needed.

11.3 Contributions

A small part of Linus' README (kernel hacking options) is inclusive. (Thanks, Linus!)

`uc@brian.lunetix.de` (Ulrich Callmeier): patch -s and xargs.

`quinlan@yggdrasil.com` (Daniel Quinlan): corrections and additions in many sections.

`nat@nataa.frmug.fr.net` (Nat Makarevitch): mrproper, tar -p

`boldt@math.ucsb.edu` (Axel Boldt): collected descriptions of kernel configuration options on the net; then provided me with the list

`lembark@wrkhors.psyber.com` (Steve Lembark): multiple boot suggestion

`kbriggs@earwax.pd.uwa.edu.au` (Keith Briggs): some corrections and suggestions

`Eric.Dumas@emi.u-bordeaux.fr` (Eric Dumas): French translation

`donahue@tiber.nist.gov` (Michael J Donahue): typos, winner of the "sliced bread competition"

`rms@gnu.ai.mit.edu` (Richard Stallman): "free" documentation concept/distribution notice

`dak@Pool.Informatik.RWTH-Aachen.DE` (David Kastrup): NFS thing

The people who have sent me mail with questions and problems have also been quite helpful.

11.4 Copyright notice, License, and all that stuff

Copyright © Brian Ward, 1994, 1995.

Permission is granted to make and distribute copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the derived work is distributed under the terms of a permission notice identical to this one. Translations fall under the catagory of "modified versions."

Warranty: None.

Recommendations: Commercial redistribution is allowed and encouraged; however, it is strongly recommended that the redistributor contact the author before the redistribution, in the interest of keeping things up-to-date. For the latter purpose, translators are also advised to contact the author beforehand. The printed version looks nicer, and remember to recycle.